SEALFAST
THE SIMPLE SOLUTION

NEW PRODUCT



SIZES
2" x 2 1/2"
2 1/2" x 2"

TYPE CR - Female Coupler x Reducing Shank

COUPLINGS+

PRODUCT LINE

TYPE CR - Female Coupler x Reducing Shank



TYPE CR

Size	WORKING PSI	ALUMINUM Part #	316 SS Part #	316 SS - Locking Part #
1-1/2" x 1"	100	CR 1510AL	CR 1510SS	---
2" x 1"	---	CR 2010AL	---	---
2" x 1-1/4"	150	CR 2012AL	---	---
2" x 1-1/2"	150	CR 2015AL	CR 2015SS	---
New 2" x 2-1/2"	150	CR 2025AL	---	---
2-1/2" x 1-1/2"	150	CR 2515AL	---	---
New 2-1/2" x 2-"	150	CR 2520AL	---	---
3 x 2"	100	CR 3020AL	CR 3020SS	---
3" x 2-1/2"	150	CR 3025AL	CR 3025SS	CR 3025SSSK
3" x 4"	150	CR 4040AL	---	---
4" x 3"	150	CR 4030AL	CR 4030SS	---

WARNING: Cam & Groove Couplings should **NOT** be used with any compressed gas, including steam or air. Metal fittings should not be used with Polypropylene Cam & Groove. Working Pressures may vary depending on how the couplings are attached to the hose assembly. Before operation, always check the hose assembly for proper attachment and that couplings are in working order.

BUY NOW

https://products.sealfast.com/item/type-cr/aluminum-cr-reducing-c-cam-and-groove-couplings/cr-2520al

The SIMPLE SOLUTION

sales@sealfast.com 800.231.0734 sealfast.com 8609 City Park Loop, Houston, TX 77013