SEALFAST
THE SIMPLE SOLUTION

NEW PRODUCT

SIZES 1 1/4" 2 1/2"



CRIMPTEK - Combo Nipples - Grooved

COUPLINGS +

PRODUCT LINE

CRIMPTEK - Combo Nipples



GROOVED

	Size	WORKING PSI	STEEL * Part #	316 SS * Part #
	1"	200	SF100SGC	SF100SSG6C
New	1-1/4"	200	SF125SGC	SF125SSG6C
	1-1/2"	200	SF150SGC	SF150SSG6C
	2"	200	SF200SGC	SF200SSG6C
New	2-1/2"	200	SF250SGC	SF250SSG6C
	3"	200	SF300SGC	SF300SSG6C
	4"	200	SF400SGC	SF400SSG6C
	6"	200	SF600SGC	SF600SSG6C

* WARNING: Working Pressures may vary depending on how the couplings are attached to the hose the hose assembly for proper attachment and that couplings are in working order.

General Uses:

Working pressures may vary with hose type and clamping system used to install couplings. Combination Nipples are recommended for low pressure discharge and suction service for compatible liquids. NOT for compressible products such as Air, Nitrogen and Steam. *All blank end & grooved combination nipples are made using Schedule 40 pipe. Seal Fast Crimp Combination Nipples are to be used with the Seal Fast Ferrules and Crimps Sleeves on pages 36-39 of this catalog. They are designed with an Interlock System which allows the Ferrule to be permanently attached to the coupling. **WORKING PRESSURE 200 PSI**

BUY NOW

sealfast.com/category/grooved

The SIMPLE SOLUTION

sales@sealfast.com 800.231.0734 sealfast.com 8609 City Park Loop, Houston, TX 77013